

Data Sheet **Open Grid PVC Matting**

Data Sheet Type	Final
Material Reference	Open Grid PVC Matting
Polymer	PVC
Date Issued	01/06/26



Description

A hard wearing lightweight open grid matting that is ideal for applications where areas are wet and slippery, or where you need to be able to remove and re-lay quickly for cleaning.

The PVC material is anti-microbial and anti-fungal and is resistant to most chemicals and cleaning agents.

Specifications	Values	Test Methods
Fungal Resistance	Yes	None
Highest Recommended Working Temperature	60 °C	None
Lowest Recommended Working Temperature	-22 °C	None

Purposes



Chemical Resistant



Food Contact Suitability

Important Notes about this Material Data Sheet

This datasheet has been carefully compiled to advise you, our customer, in the best possible way. The information, figures, test values, and data correspond to actual engineering standards and are the result of many years of tests and trials. As individual operating conditions influence the application of each product, the information supplied in this datasheet can only be seen as a rough guideline. In every case it is the sole responsibility of the customer to evaluate his individual requirements, in particular whether the specified properties of our products are sufficient for the intended use. This datasheet is subject to alteration without prior notice. All mentioned values contained herein are guiding values representing long-term experience averages. Please be aware that Test Results for individual Material Batches will only be provided if requested at the time of order and may be subject to additional charges and/or lead times. This Data Sheet supersedes all previous data sheets and any other data previously provided either Verbally, Electronic or Written, with reference to the above Material Grade.